



# MINI M-70LF



shown:  
MINI S-70LF (stainless steel) Black  
MINI M-75LF (bronze) White



## LOW-FLOW WATER SAVING TRIGGER NOZZLE

### THE WATER EFFICIENT WASH DOWN NOZZLE FOR MAXIMUM WATER SAVINGS

The **Mini M-70LF Series** is designed for heavy duty cleaning in all industrial applications, and is suitable for both hot and cold wash down applications. This compact and easy to handle spray nozzle weighs only 0.8 kg yet it provides the same high quality product expected from the industry proven range of Strahman wash down equipment, whereby utilising the same modern and innovative engineering principles and premium quality parts.

Derived from the same family of Strahman premium heavy duty M-70 Series Nozzles, the **Mini M-70LF Series** by Spray Nozzle Engineering is a water efficient spray nozzle designed to reduce potential water wastage by providing an optimum cleaning performance at lower flow rates, suitable for most industrial wash down applications.

Unlike most wash down guns typically utilised throughout the industry, the **Mini M-70LF series** offers the water saving benefits without compromising on performance. With adjustable spray pattern controlled by the trigger, you have the flexibility to vary and control the spray on demand while its ergonomic design via the palm trigger reduces operator fatigue during prolonged use.

The **Mini M-70LF Series** is accredited with the Smart Approved WaterMark, Australia's outdoor water saving labelling program, and has been assessed by an independent expert technical panel to be a true water efficient product.

- Consistent spray pattern changes even at low flow rates
- Long handle design grip for whole hand placement
- Available in Bronze or Full Stainless Steel Construction
- Instant 'Water Shut-Off System' ensure no water loss after the trigger is released
- Stainless Steel seat design stops water leakage at nozzle seat
- Heavy Duty replaceable rubber cover, available in Black or White

#### Technical Data

- Maximum working pressure = 10 Bar
- Maximum recommended operating temperature = 93°C
- Includes either 1/2" or 3/4" swivel hose barb fitting as standard (must specify size required on order)
- Fully serviceable with readily available parts and service kits

#### Available Models

- MINI M-70LF** (bronze) Black
- MINI M-75LF** (bronze) White
- MINI S-70LF** (stainless steel) Black
- MINI S-75LF** (stainless steel) white



#### Theoretical Pressure vs Flowrate for MINI M-70LF

Pressure (Bar)	0.5	1.0	2.0	3.0	4.0	5.0	6.5	10.0
Flowrate (ℓ/min)	4.5	5.0	6.2	7.3	8.5	9.5	10.5	13.5



ESC VEET APPROVED PRODUCT  
(35-LOW FLOW TRIGGER NOZZLE)



SNE80088-JUN14